



Mesotherapy needle specifications

Product:	Mesotherapy needles
Cannula:	Stainless steel AISI 304, raw, bright. drawn
Connection for siryng:	In polipropylene resin hot printed
Conicity:	Luer Lock, rules UNI 001/67
Glue:	cannula is glued with Loctite FMD11/1811 kiln-dried
Colours:	Various, it depends on Gauge international standard
Sterilization:	with Etilene oxide gas
Packaging:	single blister made of medical paper, porous ness controlled 100 needles/box
Validity:	5 years in sealed packaging
Sizes 27 Gauge:	outside diameter 0.40 mm inside diameter 0.20 mm lenght 4mm (COD: AAL4) - 6 mm (COD : AAL6) (tolerance +/- 10%)
Sizes 30 Gauge:	outside diameter 0.30 mm inside diameter 0.15 mm lenght 4mm (COD: AAL34) - 6 mm (COD : AAL36) (tolerance +/- 10%)
Sizes 32 Gauge:	outside diameter 0.26 mm inside diameter 0.11 mm lenght 4 (COD:AM 324)- 6 (COD AM 326)- 12.7 mm (COD AM32G) (tolerance +/- 10%)
Distributor:	Inthesys 2000 SAS - 20091 BRESSO (Milano)
Manufactured:	In Italy - EC
Conformity:	Directive 93/42 ECC (brought about Dlgs. 46 del 24/02/97) attached I
Provisions:	EN 556, EN 550, EN 1441, ISO 10993-5, 10, 11, EN 1633-1
CE certification:	N. 0476 (CERMET) EC CERTIFICATE N. MED-22009 valid until 2nd March 2007
Class:	Classe II A